



DIESEL 15000 TE SILENCE AVR

PORTABLE POWER

Generating Sets Range DIESEL

PRODUCT ADVANTAGES

- · Entire group guaranteed 3 years
- · KOHLER air-cooled industrial engine
- · Very Silent
- Connection interface equipped with an hour meter.
- · Hydrocarbons bulk tank

This genset is quiet and compact and features easy-to-reach components for simplified maintenance.

The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature

Range DIESEL

Both long run times and very long life for professional applications.



















This product meets the Qualigen charter, which aims to ϵ level of quality and guarantee the safety of users. Qualig commitment to safety and quality.

DIESEL 15000 TE SILENCE AVR

GENERAL SPECIFICATIONS

Range	DIESEL
Frequency (Hz)	50 Hz
Max power (kW) *	10
Max power (kVA)	12.50
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Diesel Fuel
Tank (L)	27
75% cons. (I/h) *	2.10
75% Autonomy (h) *	12.90
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	81
Acoustic pressure level @7m in dB(A)	67

ENGINE SPECIFICATIONS

Engine brand	KOHLER DIESEL
Engine ref.	KD425-2
Distribution	Diesel O.H.V.
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	851
Oil system capacity including filters (L)	2.60

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	Yes
Indication of protection	IP 23
Insulation class	Н

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + APM202

DIMENSIONS AND WEIGHT

Length (cm)	118.30
Width (cm)	67.30
Height (cm)	96
Dry Weight (kg)	275

PACKAGING

Packaging type	Box
Length (cm)	120
Width (cm)	69
Height (cm)	94
Weight (kg)	278
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0



5/1/2018





DIESEL 15000 TE SILENCE AVR

ACCESSORIES SUPPLIED



User and maintenance manual



Lifting eye

RPM



Male plugs for all models made up of: 2 x 16 A/230 V, EEC17: 1 x

16A/230 V, 1 x 32A/230 V and 1 x 16A/400V

Battery without maintenance

Hour meter

OPTIONS



