



Dishwashing

Concept Series - Frontal

DISHWASHER, FI-30

DIMENSIONS

		<u>Article</u>	<u>Packed</u>
Length	mm	600,00	700,00
Depth	mm	600,00	630,00
Height	mm	820,00	885,00
Weigth	Kg	54,00	61,00
Volumen	m3	0,30	0,39

ELECTRICITY

<u>Electric power</u>	KW	
230V -1+N		2x2,5+T - 20 A
230V - III		3x2,5+T - 20 A
400V - III+N		4x2,5+T - 20 A

WATER

Water consumption (lit/h)	41,00
Pressure (Kg/cm2)	2 - 4

GAS

Not used

STEAM

Not used

AIR

Not used

LEVEL SOUND

(dB) **65**

Certificate EQNET- CE

SGS-2199-0192-1

DISHWASHER, FI-30

Made of stainless steel.
 Hourly production: 320 dishes/h.
 Maximum diameter of dishes: Ø 32 cm.
 Wash cycle: 0-240".
 Rotating wash and rinse.
 Heated by means of shielded elements.
 Built-in rinse water boiler.
 Tank with 2.8 kW heating element.
 Tank capacity: 25 litres.
 Boiler with 2.8 KW heating element.
 Water consumption: 2.7 litres/rinse.
 Automatic rinse dispenser.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Safety thermostat.
 Safety switch for door opening.
 Adjustable legs.
 Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 1 cutlery containers.
 Power: 3.45 kW.
 Dimensions: 600 x 600 x 810 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	210	50	65		Prever Interruptor diferencial
DRAIN	370	50	65	30x25	
SOFT COLD WATER	305	50	65	3/4"	Prever llave de corte en la toma

